



Safety Data Sheet C-MUL®

SECTION 1 – IDENTIFICATION

PRODUCT NAME: C-MUL®
EFFECTIVE DATE: August 1, 2018
CHEMICAL FAMILY: Drilling Fluid Additive

MANUFACTURER: SUN DRILLING PRODUCTS CORP.
d/b/a SUN SPECIALTY PRODUCTS
503 Main Street
Belle Chasse, LA 70037

CANADIAN IMPORTER : SUN DRILLING PRODUCTS CORP.
d/b/a SUN SPECIALTY PRODUCTS
#102 6660 Taylor Drive
Red Deer, AB TYP IY3
(403)341-5046 (for 24-hr Emergency call Chemtrec)

CHEMICAL EMERGENCY – Spill, Leak, Fire, Accident
CHEMTREC USA/Canada Call 1-800 424-9300

SECTION 2 – HAZARD IDENTIFICATION

CLASSIFICATION: CATEGORY 1: ASPIRATION HAZARD
CATEGORY 1A: SKIN SENSITIZATION
CATEGORY 2: SERIOUS EYE DAMAGE, IRRITATION
CATEGORY 4 ACUTE TOXICITY (INHALATION)

LABELLING:



Signal Word - DANGER

Hazard statements

H304 - May be fatal if swallowed and enters airways
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled

Precautionary statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P331 - Do NOT induce vomiting
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray



Safety Data Sheet C-MUL®

P264 - Wash face, hands and any exposed skin thoroughly after handling
P272 - Contaminated work clothing should not be allowed out of the workplace
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention
P337 + P313 - If eye irritation persists: Get medical advice/attention
P363 - Wash contaminated clothing before reuse
P501 - Dispose of contents/ container to an approved waste disposal plant
Hazards not otherwise classified
None known
Unknown acute toxicity <1% of the mixture consists of ingredient(s) of unknown toxicity.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	PERCENT	CAS NUMBER	PEL
1-Dodecene, dimer	75-95	62132-67-6	
Distillates (petroleum), hydrotreated heavy naphthenic	2.0-8.0	64742-52-5	
Fatty acid amide	2.0-8.0	Proprietary	
Fatty acids, tall-oil, reaction products with Diethylenetriamine	.08-0.4	61790-69-0	

The criteria for listing components in the composition are as follows: Carcinogens are listed when present at 0.1% or greater; components which are otherwise hazardous according to OSHA are listed when present at 1.0% or greater. Non-hazardous components may be listed at 3.0% or greater if not proprietary in nature. This is not intended to be complete compositional disclosure. Refer to section 14 for applicable states right-to-know and other regulatory information.

SECTION 4 – FIRST AID MEASURES

EYE CONTACT - In case of eye contact, flush immediately with water for a minimum of 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove contact lenses. Seek medical attention if irritation persists.

SKIN CONTACT –Wash contaminated skin thoroughly with soap and water, and remove contaminated clothing and shoes. Get medical attention if symptoms occur. Clean clothing and shoes thoroughly before reuse.

INHALATION - If respiratory irritation develops or if breathing becomes difficult, remove to fresh air. Get medical attention if adverse health effects persist or are severe.

INGESTION - If swallowed, do NOT induce vomiting. Aspiration hazard if swallowed, can enter lungs and cause damage. Wash mouth out with water, seek immediate medical attention.



Safety Data Sheet C-MUL®

SECTION 5 – FIRE FIGHTING MEASURES

FLASHPOINT: >201°F (>94°C)

EXTINGUISHING MEDIA: Use dry chemical, carbon dioxide, or foam. Water fog can be used but water jet is not recommended.

DECOMPOSITION PRODUCTS: Smoke may contain carbon dioxide, carbon monoxide, nitrogen oxides, ammonia.

LOWER FLAME LIMIT: NA

HIGHER FLAME LIMIT: NA

UNUSUAL FIRE AND EXPLOSION HAZARDS: Excessive ambient temperature may cause a pressure rise in sealed containers; cool containers using water spray. Keep unnecessary people away.

FIRE FIGHTING EQUIPMENT: Fire Fighters and others exposed to products of combustion should wear self-contained breathing apparatus. Equipment should be thoroughly decontaminated after use.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

CHEMICAL EMERGENCY NUMBER (24 HOURS): CHEMTREC 1-800-424-9300 USA/CANADA

SPILL: In case of spill, evacuate and ventilate surrounding area. Keep unnecessary and unprotected personnel away from area of spill. Cleanup personnel should wear suitable personal protective equipment and take precautions against slipping on product. If product cannot be collected by liquids vacuum and recycled, absorb with inert non-combustible absorbent material (e.g., sand, earth, diatomaceous earth, vermiculite) and dispose of in accordance with applicable regulations. Product as sold would be a nonhazardous industrial waste. Avoid spillage into all drains, soil surfaces, and ground water. Spills causing environmental pollution must be reported to the relevant authorities.

RCRA STATUS: As sold, product is not a Characteristic or Listed RCRA hazardous waste.

SECTION 7 – HANDLING AND STORAGE

Handle in accordance with good industrial hygiene and safety practices. These practices include adequate ventilation, avoiding unnecessary exposure, using appropriate personal protective equipment when necessary, and prompt removal of material from eyes, skin and clothing. Good housekeeping is essential in reducing slipping hazards; avoid walking through spilled material. Do not reuse container.

HANDLING AND STORAGE: Store away from oxidizers, in original container protected from sunlight in dry, cool, and well-ventilated area. Provide sufficient general ventilation during and after application. Avoid prolonged or repeated contact with skin, eyes and clothing. After handling this product, wash hands before eating, drinking or smoking. If necessary, take first aid action shown in Section 4.

SECTION 8 – EXPOSURE CONTROL/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see section 3), job activities, and other substances in the work place when designing engineering controls and selecting protective equipment. There is an occupational exposure limit (OEL) for oil mists at the workplace of 5 mg/m³ based on the recommendation of the American Congress of Governmental Hygienists (ACGIH) that should be followed.



Safety Data Sheet C-MUL®

EYE PROTECTION: Chemical goggles are recommended. Goggles, or at a minimum faceshields in combination with safety glasses should be worn during transfer operations or when there is a likelihood of misting, splashing or spraying of this material.

RESPIRATORY PROTECTION: Not normally needed. Use NIOSH-approved respirator for organic vapors if exposure is unknown or causes discomfort.

PROTECTIVE GLOVES: Wear protective gloves (suggested are PVC, neoprene, nitrile rubber) if irritating to skin. Check gloves frequently during prolonged use for breakthrough.

VENTILATION: General or Local exhaust.

LOCAL EXHAUST: Recommended in circumstances where general ventilation is limited, or where respiratory irritation occurs.

Use NIOSH/MSHA approved respiratory protection equipment when airborne exposure limits are exceeded (see below). Consult the respirator manufacturer to determine appropriate type of equipment for a given application. Observe respirator use limitations specified by NIOSH/MSHA or the manufacturer. Respiratory protection programs must comply with 29 CFR 1910.134.

VENTILATION NOTES: Provide general or local ventilation to control exposure levels. The use of local mechanical exhaust ventilation is preferred at sources of air contamination such as open process equipment. Consult NFPA Standard 91 for design of exhaust systems.

THRESHOLD LIMIT VALUE: None established for this Product.

PROTECTIVE EQUIPMENT: Splash goggles, gloves, apron

The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/ODOR:	Gold to Amber Liquid/Oily Odor
ODOR THRESHOLD:	ND
pH:	ND
MELTING POINT:	350°F
FREEZING POINT:	<0°F
BOILING POINT:	ND
FLASHPOINT:	>201°F (>94°C)
EVAPORATION RATE:	NA
FLAMMABILITY (SOLID, GAS):	NA
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS:	NA
VAPOR PRESSURE:	ND
VAPOR DENSITY (AIR = 1):	NA
DENSITY	7.5 lbs/gallon (900 kg/m ³)
SPECIFIC GRAVITY	0.80 g/cc
SOLUBILITY IN WATER:	Water Dispersible
PARTITION COEFFICIENT: N-OCTANOL/WATER	
AUTO-IGNITION TEMPERATURE:	ND
DECOMPOSITION TEMPERATURE:	ND
VISCOSITY, SUS@100°F:	NA



Safety Data Sheet C-MUL®

SECTION 10 – STABILITY AND REACTIVITY

REACTIVITY:	This material is chemically stable.
CHEMICAL STABILITY:	Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
HAZARDOUS POLYMERIZATION:	Under normal conditions of storage and use, hazardous polymerizations will not occur.
CONDITIONS TO AVOID:	Keep away from heat and direct sunlight. Recommended storage temperature should not exceed 122° F (50° C). Do not freeze.
INCOMPATIBLE MATERIALS:	Avoid contact with oxidizing materials.

SECTION 11 – TOXICOLOGICAL INFORMATION

ACUTE TOXICITY:

INGESTION: May be fatal if swallowed and enters airways. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

INHALATION: Vapors may irritate throat and respiratory system. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination. Prolonged overexposure through inhalation can be harmful to health.

SKIN CORROSION/IRRITATION: Persons with pre-existing skin disorders may experience irritation. Repeated exposure may cause skin dryness and/or cracking. Direct contact with product may cause an allergic skin reaction.

SERIOUS EYE DAMAGE/IRRITATION: May cause serious eye irritation. May cause redness, itching, and pain on direct contact.

RESPIRATORY OR SKIN SENSITIZATION: May cause skin sensitization.

MUTAGENICITY: ND; no component of this product at levels >0.1% is classified by established regulatory criteria as a mutagen.

CARCINOGENICITY: ND; no component of this product at levels >0.1% is classified by ACGIH, IARC, or the European Commission as a carcinogen.

REPRODUCTIVE TOXICITY: ND; no component of this product at levels >0.1% is classified by established regulatory criteria as teratogenic or embryotoxic.

ASPIRATION HAZARD: May be fatal if swallowed and enters airways.

SECTION 12 – ECOLOGICAL INFORMATION

Chemical Name	Toxicity to fish	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates
Distillates (petroleum), hydrotreated heavy naphthenic	>5000 mg/L LC50 Oncorhynchus mykiss 96 hr	No information available	> 1000 mg/L EC50 Daphnia magna 48 hr
Fatty acid amide	No information available	No information available	No information available
Fatty acids, tall-oil, reaction products with diethylenetriamine	No information available	No information available	No information available

PERSISTENCE & DEGRADABILITY: ND

BIOACCUMULATIVE POTENTIAL: ND



Safety Data Sheet C-MUL®

MOBILITY IN SOIL: This product is not likely to move rapidly with surface or groundwater flows because of its low water solubility.

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Follow applicable governing regulations for disposal. Product as sold is not a Listed or Characteristic waste per RCRA.

SECTION 14 – TRANSPORTATION INFORMATION

The data provided in this section is for information only. The description shown may not apply to all shipping situations. Consult 49 CFR, or appropriate regulations to properly classify your shipment for transportation.

UN PROPER SHIPPING NAME:	NON-REGULATED
TRANSPORT HAZARD CLASS AND LABEL:	N/A
UN/NA NUMBER:	N/A
HARMONIZED CODE/TARIFF CODE	3902-90-0050
PACKAGING SIZE:	55-gallon drums; 275-gallon disposable tote tanks; 550-gallon rig storage bulk containers
REPORTABLE QUANTITY:	This material does not contain any chemicals with CERCLA Reportable Quantities.

SECTION 15 – REGULATORY INFORMATION

SARA 311 CATEGORIES:

EPA ACUTE:	Yes
EPA CHRONIC:	No
EPA IGNITABILITY:	No
EPA REACTIVITY:	No
EPA SUDDEN RELEASE OF PRESSURE:	No
CERCLA RQ VALUE:	None under CERCLA but check individual State Regulations.

SARA TPQ:	None
SARA RQ:	NA
SARA SECTION 313:	No
EPA HAZARD WASTE#:	None
CLEAN AIR:	N/A
CLEAN WATER:	N/A
DEA Chemical Trafficking Act:	N/A
TSCA STATUS:	All ingredients in this product are either listed on the U.S.TSCA Inventory, or are not regulated under TSCA.
DSL STATUS:	All components are either on the DSL, listed in NDSL, or are exempt from DSL listing requirements.



Safety Data Sheet C-MUL®

SECTION 16 – OTHER INFORMATION

FOOT NOTES: NA NOT APPLICABLE
> = GREATER THAN OR EQUAL TO

ND – NO DATA AVAILABLE
< = LESS THAN OR EQUAL TO

REVISION DATE: August 1, 2018

REVISION STATEMENT: Changes have been made throughout this Safety Data Sheet. Please read the entire document.

DISCLAIMER:

Although the information and recommendations set forth herein (hereinafter “Information”) are presented in good faith and believed to be correct as of the date hereof, the Company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving this SDS will make their own determination as to its suitability for their intended purpose prior to use. Since the product is within the exclusive control of the user, it is the user’s obligation to determine the conditions of safe use of this product. Such conditions should comply with all Federal Regulations concerning the Product.

NO REPRESENTATIONS OR WARRANTIES EITHER EXPRESSED OR IMPLIED OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH THIS INFORMATION REFERS.

This is the LAST PAGE of this SDS